



SENSITIVITY	感 度
SENSITIVITY REDUCTION	感度遞減
FREQUENCY	頻 率
MAX. WORKING VOLTAGE	最大工作電壓
CURRENT CONSUMPTION	電流消耗
S/N RATIO	信 噪 比
STORAGE TEMPERATURE	儲存溫度
WEIGHT	重 量

Schematic Diagram 測定電路圖

Dimensions (Unit: mm±0.2) 尺 寸 圖

Typical Frequency Response Curve 頻率響應圖

FEATURES

特色

- Omnidirectional type 全指向性
- Ultra thin 超薄
- For GSM, PDA....Dual Band applications 適用於GSM, PDA, 雙頻機...等

OBO-45SN-5B

OBO-45KP-5B

OBO-45EN-5B

- $V_s=2.0V, R_L=2.2K\Omega$
- $-38\pm 3dB$ $-40\pm 3dB$ $-42\pm 3dB$ $-44\pm 3dB$
- $F=1KHz, 0dB=1V/Pa$ Within
- $-3dB$ at 1.5V compare to 3.0V
- 50~16,000Hz
- Max. 10V
- Max. 0.5mA
- More than 60dB
- $-25^{\circ}C$ to $+70^{\circ}C$
- Max. 1.0gm

