



DIMENSIONS	尺 寸
NOMINAL IMPEDANCE	阻 值
POWER RATING	設 定 值
LOWEST RESONANT FREQUENCY	最低頻率
OUTPUT SOUND PRESSURE LEVEL (S.P.L.)	輸出音壓
FREQUENCY RANGE	頻率範圍
DISTORTION	失真程度
OPERATING TEMP. RANGE	操作溫度
STORAGE TEMP. RANGE	儲存溫度
WEIGHT	重 量

Dimensions
(Unit: ±0.3mm)
規格尺寸圖

Frequency Response Curve
(Distance: 0.5m)
頻率響應圖

APPLICATIONS


- Headphones & Earphones
- Hands-Free Cellular Phones
- Communication Equipments

適用範圍

- 耳機專用
- 手機免持耳機
- 通訊設備

OBO-15150F-02

15.0mm x 4.2mm
150Ω ± 15% at 1,200Hz / 1.0v
Normal 30mW / Max. 50mW
500Hz ± 150Hz
99 ± 3dB / 30mW / IEC-318
Average at 1.0, 1.2, 1.5, 2.0kHz
300-20,000Hz Average SPL-10dB
5% Maximum at 1200Hz, 30mW
-25°C to +50°C
-25°C to +55°C
1.7gms



HOUSING MATERIAL : METAL

