



DIMENSIONS	尺寸
NOMINAL IMPEDANCE	阻值
POWER RATING	設定值
LOWEST RESONANT FREQUENCY	最低頻率
OUTPUT SOUND PRESSURE LEVEL (S.P.L.)	輸出音壓
FREQUENCY RANGE	頻率範圍
DISTORTION	失真程度
OPERATING TEMP. RANGE	操作溫度
STORAGE TEMP. RANGE	儲存溫度
WEIGHT	重量

Dimensions  
(Unit: ±0.2mm)  
輪廓尺寸圖

### APPLICATIONS


- Handy Video Games
- Computer Peripherals
- Electric Dictionary
- Computer Modems
- Communication Equipments

### 適用範圍

- 掌上型遊戲器
- 電腦周邊
- 電子字典
- 數據機
- 通訊設備

#### OBO-23008F-01

23.0mm×2.0mm
8Ω±15% at 1,400Hz/1.0v
Normal 200mW / Max. 500mW
750Hz±150Hz
82±3dB / 200mW / 0.5Meter
Average at 1.0, 1.2, 1.5, 2.0KHz
550~6,000Hz Average SPL-10dB
5% Maximum at 1,000Hz, 200mW
-25°C to +50°C
-25°C to +55°C
3.5gms



HOUSING MATERIAL : METAL

#### OBO-27032G-01

27.0mm×5.1mm
32Ω±15% at 1,000Hz
Normal 200mW / Max. 500mW
600Hz±150Hz
80±3dB / 200mW / 0.5Meter
Average at 1.0, 1.2, 1.5, 2.0KHz
400~7,000 Hz Average SPL-10dB
6% Maximum at 1,000Hz, 200mW
-25°C to +50°C
-25°C to +55°C
5.0gms



HOUSING MATERIAL : ABS

Frequency Response Curve  
(Distance: 0.5m)  
頻率響應圖

